

# **PRODUCT INFORMATION**

# PRIMER PR 200

## Fields of Application

TIP TOP **PRIMER PR 200** is used for preparing metal surfaces before bonding rubber to metal by means of **CEMENT SC 2000**, **CEMENT BC 3000** or **CEMENT SC 4000**.

## Product Description

Polymer Basis:	Polymeric mixture
Solvent:	Methyl ketonic isobutyl, xylene (flammable!)
Colour:	grey
Density:	0,93 g/ml
Consumption:	approx. 100 g/m²
Number of coats:	1 coat on metal
TLV:	100 ppm

#### Product Advantages

- High productivity

- Good adhesion of rubber to metal.

#### Shelf Life

1 year when storing in unopened original container under storing conditions in accordance with DIN 7716.

#### Available Packing Units

Description	Content	Product-No.
PRIMER PR 200	0.75 kg	525 2406

This data sheet is for informational purposes only. All data provided herein is based on in-depth research and testing, however no liability whatsoever can be assumed. Since we are constantly endeavouring to up-date and improve our products, we recommend noting the index and issue date indicated on this data sheet and to inquire as to whether any properties have changed in the interim. This Product Information Sheet replaces all prior issues. Please contact our Technical Consultant for detailed information in case of ambiguities.

TIP TOP Oberflächenschutz Elbe GmbH, Heuweg 4, D-06886 Wittenberg Phone: +49 (0) 34 91 / 6 35 – 50, Fax: +49 (0) 34 91 / 6 35 – 5 52

TIP TOP Oberflächenschutz Elbe GmbH	PRIMER PR 200	INDEX B of 01.01.2005
Page: 1/1	API	Replaces Issue: 01.01.2004